

COLORPRINT NEW M

Description PVC heat seal material created for inkjet digital printing & cutting systems with solvent, eco solvent or thermoresin based inks. Despite being very thin, the material grants a high covering power on dark fabrics.
Average film thickness before application: **120 micron**

Basic information Due to the many different base materials available on the market, the following instructions are given as a guideline only :
Plotter settings (eg. with ROLAND VP-300)
Blade: **new at 50°**
Minimum required pressure: **50 gf**
Transfer setup
Temperature: **165°C** (330°F)
Time: **15"**
Pressure: **medium (3÷4 bar)**

Application instructions

Print and cut the material
Let the print dry at least 12 hours before rolling, overlaying or heat transferring the material
Weed the exceeding material
Remove the print from the paper backing using Siser's T.T.D. (adhesive, transparent and resistant to high temperatures)
Heat apply
Remove the application tape warm (should you use other application tapes, follow the manufacturer's instructions)

Suitable textiles Cotton, polyester and blends of these materials
(not suited for treated and dye sublimation fabrics)

Washing instructions Wait **24h** after the heat transfer
60°C Max- inside out
Do not use bleach or other aggressive chemical agents.
Dry clean: **no**
Tumble dry: **not recommended**

**Siser s.r.l.**

Viale della Tecnica n° 18
36100 Vicenza - Italy
Tel. +39 0444.287960
Fax +39 0444.287959
info@siser.it - www.siser.it

r.e.a. vi 171856 - reg. imp. vi n° 14971
c.s. € 103.300 i.v. - p.iva 01591490246

N.B.

All information given in this sheet are based on our experience.
We always recommend performing a test before starting standard production.
For best results we recommend to store the product away from direct sunlight.

The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).
This document can be subject to variations. Updated versions are available on our website www.siser.it.
For further information, please contact our Sales Office.
Thank you.